

DIAL CALIPERS

SHOCK
PROOF

INSPECTION
CERTIFICATE
TRACEABLE TO DKD




- Shockproof dial indicator
- Made of stainless steel

1312-150A

Dial indicator graduation: 0.02mm

(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d	D	t
1312-150A *	0-150mm	±0.03mm	with	235	21	16.5	16	40	Ø39	6.5
1312-200A *	0-200mm	±0.03mm	with	288	24	19	16	48	Ø39	6.5
1312-300A *	0-300mm	±0.03mm	with	410	28	22	20	62	Ø44.5	7.5
1312-100AW *	0-100mm	±0.02mm	without	165	18	13	13	30	Ø32	6
1312-150AW *	0-150mm	±0.03mm	without	235	21	16.5	16	40	Ø39	6.5
1312-200AW *	0-200mm	±0.03mm	without	288	24	19	16	48	Ø39	6.5
1312-300AW *	0-300mm	±0.03mm	without	410	28	22	20	62	Ø44.5	7.5



Dial indicator graduation: 0.01mm

(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d	D	t
1311-150A *	0-150mm	±0.03mm	with	235	21	16.5	16	40	Ø39	6.5
1311-200A *	0-200mm	±0.03mm	with	288	24	19	16	48	Ø39	6.5
1311-300A *	0-300mm	±0.03mm	with	410	28	22	20	62	Ø44.5	7.5
1311-150AW *	0-150mm	±0.03mm	without	235	21	16.5	16	40	Ø39	6.5
1311-200AW *	0-200mm	±0.03mm	without	288	24	19	16	48	Ø39	6.5
1311-300AW *	0-300mm	±0.03mm	without	410	28	22	20	62	Ø44.5	7.5

* Supplied with manufacturer inspection certificate traceable to DKD Germany